

# COMMERCIAL SECURITY SAFES

## CSC SERIES COMPOSITE SAFES



American Security CSC SERIES COMPOSITE SAFES are an affordable solution when you want to protect both documents from fire and valuables from burglary attacks. During extreme testing procedures the CSC SERIES COMPOSITE safes passed a 2-Hour, 350°F internal and 1700°F external factory fire test certification. UL listed RSC Level I.

### DOOR FEATURES

- Overall thickness of 4-5/8" and is constructed with a 2" defense barrier of outer and inner steel plates creating a burglary resistant structure enclosing a unique proprietary, fire resistant material

### BODY FEATURES

- 2-7/8" double wall steel construction enclosing a unique, high-density fire and burglary resistant composite material
- Durable powder coated adjustable shelves
- Fire Endurance: 2 hour, 350°F factory fire rating. Tested at temperatures up to 1700°F
- Heat expandable intumescent door seal guards contents against severe fires

### LOCKING MECHANISM FEATURES

- Two to four 1-1/2" diameter solid steel chrome-plated locking bolts
- Two to three 1-1/2" diameter solid steel dead bolts lock deep into body preventing door removal during a forced entry attempt
- U.L. Listed ESL10 or Group II combination lock with chrome-plated spy-proof dial. Optional electronic locks available
- Lock protected by a tempered glass relock device
- Heavy duty steel hinges provide easy, smooth door operation
- One internal counter-sunk anchor hole and mounting hardware are provided to securely anchor safe
- Attractively accented with a full width fascia panel and matching three point handle
- Durable and attractive charcoal gray textured finish

Optional Stor-It cabinets available in models CSC3018 and CSC4520. No kit needed, drawers slide right in.

Optional 8" LED light kit with motion sensor available for all models. See page 10 for details.



CSC4520



CSC1413



CSC1913



CSC3018

Model	Outside Dimension H" x W" x D"	Inside Dimension H" x W" x D"	Door Clearance H" x W"	Door Thickness	Body Thickness	Cubic Capacity	Weight	Lock Type
CSC1413	19-1/2 x 18 x 19-7/8	14 x 12-1/2 x 12-1/4	14 x 12-1/2	2	2-3/4	2,135	256 lbs.	Spy-proof dial, ESL10
CSC1913	24-1/2 x 18 x 19-7/8	19 x 12-3/8 x 12	19 x 12-3/8	2	2-3/4	2,898	318 lbs.	Spy-proof dial, ESL10
CSC3018	35-1/2 x 23-1/2 x 24	30 x 18 x 16-1/2	30 x 18	2	2-3/4	8,802	496 lbs.	Spy-proof dial, ESL10
CSC4520	50-1/2 x 25-1/2 x 28-7/8	45 x 20 x 21-1/4	45 x 20	2	2-3/4	19,080	728 lbs.	Spy-proof dial, ESL10

Add 2" to outside depth for handle, dial and hinge projection. Add 4/4" (casters) and 1" (rubber feet) to outside height.