WALL SAFES

American Security WALL SAFES are designed to provide hidden protection for documents and miscellaneous valuables. Each wall safe is also designed for easy installation between 16" o/c wall studs. Pre-drilled anchor holes and a built-in flange eliminates unnecessary replastering.

WEST 2114 FEATURES

- Extra spacious interior, while still offering the convenience of fitting between studs
- DL6000 bounce-proof electronic lock with a LCD display allows smooth and easy operation
- LCD display shows low-battery indicator, time, date and keypad
- Emergency key-lock override system with two (2) keys, power override battery box, built-in spy-proof function and motion detector alert
- Heavy gauge solid steel construction, plus dual live bolts made also of heavy gauge steel

- Carpeted base
- Pry-resistant recessed door with internal hinges for anti-theft protection
- Two removable shelves
 Cream colored, durable powder coated finish
- Packaged for UPS shipment

HEAVY-DUTY WS1214E5 FEATURES

- An additional spring-loaded relocking device, activated by a punching attack
- Lock and relocks are protected by a large carburized hardplate
- Handle activated locking mechanism consisting of three 1" diameter locking bolts. Each bolt is drive resistant, chromed steel with a long throw
- One piece heavy duty dead bar behind hinge prevents removal of door even if hinges are removed during a forced entry attempt
- Two removable shelves. Extra deep interior
 American Security's U.L.- Listed ESL5
- electronic lock

HEAVY-DUTY WFS149E5LP FEATURES

- U.L. Listed one hour fire rating, ensuring the inside temperature never exceeded 350° F (paper chars at 450° F)
- Extra deep interior, with one (1) convenient drawer shelf
- American Security's U.L.-Listed ESL5
 electronic lock
- Each safe is equipped with side locking boltwork mechanism incorporating ½" steel deadbolts
- Impressive ½" thick door with attractive Black Granite finish



WFS149E5LP



WS1214E5



WEST2114

Model	Outside Dimension H" x W" x D"	Inside Dimension H" x W" x D"	Door Clearance H" x W"	Door Thickness	Body Thickness	Cubic Capacity	Weight	Lock Type
WFS149E5LP*	19-½ x 14 x 15-¾	15-¼ x 9-¾ x 9-7⁄8	15-¼ x 9-¾	3	2-1⁄8	1,468	104 lbs.	ESL5LP
WS1214E5	12-% x 14 x 10	12-¼ x 13-5⁄8 x 5-¼	10-¾ x 11-¼	3⁄4	7 GA	876	86 lbs.	ESL5
WEST2114	21-1⁄8 x 13-7⁄8 x 4	20-7⁄8 x 13-3⁄4 x 2-7⁄8	19-¼ x 10-¼	7 GA	14 GA	733	31 lbs.	DL6000

* 350° F, U.L. Listed, 1-Hr fire rated wall safe.

