DS SERIES "B" RATE ROTARY & FRONT LOADING

DST2014

DSF2014

American Security's DS Series Depository Safes are designed to provide immediate deposits and storage for cash, jewelry and miscellaneous valuables.

Deposits can be made to a locked compartment via a top-loading rotary hopper, a reverse or a front-loading deposit door.



BODY

- Strong, formed "B" Rate construction made of A36 solid steel plate for improved security and appearance
- Formed door jamb for increased resistance to sledgehammer attack
- Four anchor bolt holes are standard

DOOR MODEL NUMBERS: 2014, 2714 & 3214

- 1/2" thick A36 solid steel plate, recessed 1/2" to increase resistance to pry attack
- Three 1" diameter chromed steel locking bolts
- Bolt detent system engages boltwork automatically
- Auxiliary spring-loaded relocking device
- Lock and relock protected by large carburized hardplate

HOPPER

- Large package sizes: (Top Load Rotary): 4-¾"D x 4-¾"W x 10"L (Front/Reverse Load): 4"D x 2-¾"W x 10-½"L
- Recessed, heavy duty ³/₁₆" construction (¼" door)
- Protected by dual "anti-fish" baffle

COLOR(S): Charcoal Gray





DSF2714



DSF3214

Model	Outside Dimension H" x W" x D"	Inside Dimension H" x W" x D"	Door Clearance H" x W"	Door Thickness	Body Thickness	Cubic Capacity	Weight	Lock Type
DST2014	20-¼ x 14 x 14	11-½ x 13-¾ x 11	9-¾ x 9-¾	1/2	11 GA	1,739	90 lbs.	ESL10
DSF2014	20-¼ x 14 x 14	10 x 13-¾ x 11	9-¾ x 9-¾	1/2	11 GA	1,513	79 lbs.	ESL10
DSF2714	27-¼ x 14 x 14	17-¼ x 13-¾ x 11	9-¾ x 9-¾	1/2	11 GA	2,609	93 lbs.	ESL10
DSF3214	32-¼ x 14 x 14	TP 11-¼ x 13-¾ x 11 BT 12-½ x 13-¾ x 11	9-¾ x 9-¾	1/2	11 GA	1,815 1,702	144 lbs.	ESL10

†Specify Prefix: T=Top Loading, F=Front Loading *Add 2" to outside depth for dial and handle projection.

