TL-15 MONEY CHESTS

DXE U.L. LISTED

American Security TL-15 U.L. Listed

with a banking rating of BR (TL-15).

offer the highest level of security

available with many outstanding features and a wide range of options.

DOOR FEATURES

BODY FEATURES

American Security MONEY CHESTS

• DXE model is TL-15 rated constructed of 1/2"

thick high-strength solid steel plate

Oil impregnated bronze bearing hinges

• DXE models: Consist of 1/2" thick steel plate

MONEY CHESTS qualify for Mercantile

& Broadform Insurance Class ER (TL-15)

(100,000 P.S.I. minimum tensile strength).
All external seams are beveled and

 Shelf strips installed allowing shelf adjustment. Shelves optional

continuously welded

LOCKING MECHANISM FEATURES

- U.L. listed Group 2M key changeable combination lock, with relock and 1 million possible combinations
- Single auxiliary spring loaded relocking device, activated by a punching attack
- Locks and relocks protected by a patented active hardplate
- A handle activated locking mechanism consisting of two to six 1" chromed steel locking bolts
- Five boltwork sizes allow American Security to build units from 12" to 88" high, widths from 14" to 41"
- Solid steel dead bar prevents door removal if hinges are removed during a forced entry attempt
- Compact locking mechanism and boltwork cover allow for optional door mounted coin racks

HINGE FEATURES

Fabricated from high strength steel with





- precision machined alloy dowel pins
- Oil impregnated bronze bearing assures easy opening doors and reduced maintenance
- Vertical height adjustment

OPTIONAL FEATURES

- · Spy proof dial
- Key lock dial
- Coin racks
- · Managers lockers
- Interior lockers
- Interior drawers
- · Adjustable shelves
- Electronic locks
- · Auxiliary Key-Op locks
- · Anchor bolt assembly
- · Left swing door
- · Internal rotary hopper
- Internal deposit slot
- Internal deposit chutes
- · Hidden compartments
- Special sizes
- Custom colors



Model	Outside Dimension H" x W" x D"	Inside Dimension H" x W" x D"	Door Clearance H" x W"	Door Thickness	Body Thickness	Cubic Capacity	Weight	Lock Type
DXE1414†	15-½ x 15-½ x 16-¼	14-½ x 14-½ x 12-¼	13-½ x 13-¼	1/2	1/2	2,523 in.	240 lbs.	See pg. 52
DXE1818†	19-½ x 19-½ x 16-¼	18-½ x 18-½ x 12-¼	17-½ x 16-¾	1/2	1/2	4,107 in.	325 lbs.	See pg. 52
DXE2020†	21-½ x 21-½ x 24-¼	20-½ x 20-½ x 20-¼	19-½ x 18-¾	1/2	1/2	8,405 in.	464 lbs.	See pg. 52
DXE2420†	25-½ x 21-½ x 24-¼	24-½ x 20-½ x 20-¼	23-½ x 18-¾	1/2	1/2	10,045 in.	513 lbs.	See pg. 52
DXE2424XD†	25-½ x 25-½ x 28-¼	24-½ x 24-½ x 24-¼	23-½ x 18-¾	1/2	1/2	14,406 in.	635 lbs.	See pg. 52
DXE3018XD†	31-½ x 19-½ x 24-¼	30-½ x 18-½ x 20-¼	29-½ x 16-¾	1/2	1/2	11,285 in.	574 lbs.	See pg. 52
DXE3024†	31-½ x 25-½ x 24-¼	30-1/2 x 24-1/2 x 20-1/4	29-½ x 16-¾	1/2	1/2	14,945 in.	673 lbs.	See pg. 52
DXE3030	31-½ x 31-½ x 24-¼	30-1/2 x 30-1/2 x 20-1/4	29-½ x 28-¾	1/2	1/2	18,605 in.	770 lbs.	See pg. 52
DXE4024	41-½ x 25-½ x 24-¼	40-½ x 24-½ x 20-¼	39-½ x 22-¾	1/2	1/2	19,845 in.	821 lbs.	See pg. 52
DXE4524	46-½ x 25-½ x 24-¼	45-½ x 24-½ x 20-¼	44-½ x 22-¾	1/2	1/2	22,295 in.	897 lbs.	See pg. 52
DXE5030	51-½ x 31-½ x 24-¼	50-½ x 30-½ x 20-¼	49-½ x 28-¾	1/2	1/2	30,805 in.	1,103 lbs.	See pg. 52
DXE5224	53-½ x 25-½ x 24-¼	52-½ x 24-½ x 20-¼	51-½ x 22-¾	1/2	1/2	25,725 in.	1,100 lbs.	See pg. 52
DXE6030	61-½ x 31-½ x 24-¼	60-½ x 30-½ x 20-¼	59-½ x 28-¾	1/2	1/2	36,905 in.	1,274 lbs.	See pg. 52
DXE7234	73-½ x 35-½ x 30-¼	72-½ x 34-½ x 26-¼	71-½ x 32-¾	1/2	1/2	65,033 in.	1,775 lbs.	See pg. 52

