

BF Series

FEATURES

- Available in a wide variety of paint finishes
- Made in the USA
- UL RSC I security rating

DOOR

- Dual seal design utilizes a silicone foam seal with a heat-expanding Palusol intumescent seal
- ½" solid steel plate door providing top rated security

BODY

- 3 massive 1" diameter solid steel chrome plated locking bolts. A full length dead bar locks deep into the body preventing door removal during a forced entry attempt
- Heavy duty steel hinges provide easy smooth door operation
- 1 recessed anchor bolt hole and mounting hardware are provided to securely anchor safe
- Plush velour interior
- BF1512, BF1716, BF2116 have 1 shelf. BF3416 has 2 shelves

- Optional storage cabinets available on models BF3416 and BF1716
- Optional BF safe pedestals available

FIRE PROTECTION

- UL fire rating of 1700°F for 60 minutes (Most respected fire rating to achieve) except BF3416 which has an ETL fire rating of 1200°F for 60 minutes
- Comes with intumescent door seal
- Lifetime fire replacement warranty
- Fire clay fill - a seamless fire-resistant barrier



BF1512

HIGH GLOSS



TEXTURED



HARDWARE



** Quotes available for other custom options such as two-tone, discontinued colors, or color match to your specifications, subject to manufacturing limitations.

Model	Outside Dimension H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Weight	Lock Type
BF1512	20¼" x 17¼" x 18¾"	15" x 12"	2⅝"	2,340 cu. in.	288 lbs.	UL Group II
BF1716	22¼" x 21¾" x 21¾"	17" x 16½"	2⅝"	4,488 cu. in.	412 lbs.	UL Group II
BF2116	26¼" x 21¾" x 20¼"	21" x 16½"	2⅝"	5,024 cu. in.	476 lbs.	UL Group II
BF3416	39¼" x 21¾" x 21¾"	34" x 16½"	2⅝"	8,976 cu. in.	690 lbs.	UL Group II