

BFS Series

ALL BFS MODELS BESIDES BFS912: FEATURES

- 1 anchor hole with hardware
- Cement-based fire and security barrier
- ESL10 UL Type 1 high security lock
- ETL fire rating of 60 minutes at 1200°F
- UL RSC 1 security rating
- ½" solid steel plate door providing top rated security
- 3-way & 4-way bolt work protecting from severe pry attacks
 - BFS2214: 3-way active bolt work, or 7 active bolts

- BFS2815, BFS3416, & BFS4520: 4-way active bolt work, or 10 active bolts
- Optional storage cabinets available on BFS4520E1

BFS912: BODY

- 1¾" double wall steel construction
- ¾" steel barrier
- Interlock fire-safe jamb
- ETL fire rating of 80 minutes at 1775°F
- 2 anchor holes with hardware

BFS912: DOOR

- ½" solid steel plate door providing top rated security
- ESL5LP, UL Type 1 high security electronic lock
- Massive hardplate and two relock devices
- (3) ¾" x 1" steel locking bolts
- (3) ¾" x 1" steel dead bolts



BFS2214



BFS912



TWO-TONE



Textured
Black &
Charcoal
Gray

HARDWARE



Chrome



BFS912E5LP



All Other
BFS Models



Model	Outside Dimension H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Weight	Lock Type
BFS1512E1	20⅞" x 17⅞" x 19⅜"	14⅞" x 12"	2⅝"	2,430 cu. in.	278 lbs.	ESL10
BFS2214E1	27⅞" x 19⅞" x 21¾"	21⅞" x 13⅞"	2⅝"	4,839 cu. in.	424 lbs.	ESL10
BFS2815E1	33" x 20" x 22¾"	27⅞" x 14⅞"	2⅝"	6,568 cu. in.	514 lbs.	ESL10
BFS3416E1	39⅞" x 21" x 23¾"	33⅞" x 15⅞"	2⅝"	9,462 cu. in.	634 lbs.	ESL10
BFS4520E1	49⅞" x 25⅞" x 25¾"	44⅞" x 19¾"	2⅝"	16,707 cu. in.	792 lbs.	ESL10
BFS912E5LP	12½" x 16" x 16⅜"	8⅞" x 12½"	1¾"	1,238 cu. in.	145 lbs.	ESL5LP