

CSC Series

FEATURES

- UL RSC1 security rating
- 2 hour factory fire rating

DOOR

- Overall thickness of 4 $\frac{3}{8}$ " and is constructed with a 2" defense barrier of outer and inner steel plates creating a burglary resistant structure enclosing a cement-based fire and security barrier

BODY

- Durable powder coated adjustable shelves
- Heat expandable intumescent door seal guards contents against severe fires

LOCKING MECHANISM

- (2-3) 1 $\frac{1}{2}$ " diameter solid steel dead bolts for protection from pry attacks
- UL Listed ESL10 or Group II combination lock with chrome-plated spy-proof dial. Optional electronic locks available

- Glass relocker provides another substantial barrier of burglary protection.
- Heavy duty steel hinges provide easy, smooth door operation
- One internal recessed anchor hole and mounting hardware are provided to securely anchor safe
- Attractively accented with a full width fascia panel and matching 3-spoke handle

TEXTURED



Textured
Charcoal
Gray

HARDWARE



Chrome



CSC1913



IMPORTANT:

- Add 2" to outside depth for handle, dial and hinge projection.
- Add 1" (rubber feet) to outside height

Model	Outside Dimension H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Weight	Lock Type
CSC1413E1	19 $\frac{1}{2}$ " x 18" x 19 $\frac{7}{8}$ "	14" x 12 $\frac{1}{2}$ "	2 $\frac{3}{4}$ "	2,135 cu. in.	256 lbs.	ESL10
CSC1913E1	24 $\frac{1}{2}$ " x 18" x 19 $\frac{7}{8}$ "	19" x 12 $\frac{3}{8}$ "	2 $\frac{3}{4}$ "	2,898 cu. in.	318 lbs.	ESL10