

UL Series

FEATURES

- Safes withstand fires of up to 1850°F for 2 hours and a 30' drop – equivalent to falling through a 2 story burning building
- The best warranty in the business. Lifetime fire replacement and 1 year parts and labor
- Increased barriers for burglary protection. Impressive 3½" thick recessed door with ⅝" thick front for excellent pry resistance
- Handle activated locking mechanism with 7/8" diameter solid steel chrome plated locking bolts offering smooth operation
- Internal anchor bolt hole with hardware
- UL Listed Group II key changeable combination lock with relock. 1 million possible combinations
- Auxiliary spring-loaded relock device activated by severe attack
- Heavy duty steel hinges provide additional security and smooth operation
- For your convenience, rubber feet are standard
- 1 adjustable shelf and one base on all models
- Attractively accented with a brass or chrome handle, decorative emblems and plush velour interior



UL1511



TEXTURED



Textured
Charcoal
Gray

HARDWARE



Chrome



Brass



IMPORTANT:

- Add 2" to outside depth for handle, dial and hinge projection. Outside height includes 1" high rubber feet, 2¾" for casters on the 2 largest models.
- Shown with optional electronic lock

Model	Outside Dimension H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Weight	Lock Type
UL1511	22" x 17" x 18½"	15¼" x 11"	2¾"	2,139 cu. in.	246 lbs.	UL Group II
UL1812	25" x 18" x 18"	18½" x 12½"	2¾"	2,775 cu. in.	272 lbs.	UL Group II
UL1812X	25" x 18" x 23½"	18½" x 12½"	2¾"	3,931 cu. in.	298 lbs.	UL Group II