

CFX Series (TL-30x6)



FEATURES

- Made in the USA
- Underwriters Laboratories TL-30x6 rating
- All 6 sides of the safe constructed with a defense barrier of inner and outer steel plates enclosing a unique interlocking heavy duty steel barrier, high strength concrete
- Filled with high strength concrete exceeding 12,000 psi combined with a high density high strength ceramic matrix. Impervious to the most sophisticated attacks.

- High density insulating materials incorporated in the door and body
- Impervious to burglary attacks attempted by the most sophisticated equipment utilized today and the vaults contents against intense fires
- Optional 3-way bolt work & glass relocker

FIRE PROTECTION

- Safes withstand fires of up to 1850°F for 2 hours



CFX452020



TEXTURED



Textured
Charcoal
Gray

HARDWARE



Satin



IMPORTANT:

- Add 2½" to outside depth for handle, dial and hinge projection.
- Optional 3-way boltwork available on the CFX line.

Model	Outside Dimension H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Weight	Lock Type
CFX252016	31" x 26" x 25¼"	25" x 20"	3"	4.6 cu. ft.	1,433 lbs.	See pg. 73
CFX352020	41" x 26" x 29¼"	35" x 20"	3"	8.1 cu. ft.	1,946 lbs.	See pg. 73
CFX452020	51" x 26" x 29¼"	45" x 20"	3"	10.4 cu. ft.	2,343 lbs.	See pg. 73
CFX582820	64" x 34" x 29¼"	58" x 28"	3"	18.8 cu. ft.	3,418 lbs.	See pg. 73
CFX703620	76" x 42" x 29¼"	70" x 36"	3"	29.2 cu. ft.	4,578 lbs.	See pg. 73